



SPECIFICATIONS

TORQUE SPECIFICATIONS

Description	N-m	Lb-Ft
Bearing Retainer	15-27	11-20
Shift Cover	8-15	6-11
Turret Cover	17-20	12-15
Drain Plug	17-29	12-22
Transmission to Flywheel Housing	61-88	45-65
Speedometer Cable Retaining Screw	6-13	54-115 (Lb-In)
Transmission Support	48-68	36-50
Transmission Extension Housing Bolts	47-61	30-45
Driveshaft Nuts	56-77	42-57
Catalytic Converter Retaining Bolts	27-41	20-30
Shift Lever to Transmission	31-43	23-32
Shift Boot to Floorpan	4.1-9.5	3-7
Cluster Gear Rear Bearing Retainer	15-27	11-20
Top Gear Sensing Switch	17-24	12-18
Backup Lamp Switch	27-47	20-35
Neutral Sensing Switch	27-47	20-35
Fifth/Reverse Shift Lever Pivot Pin	15-27	11-20
Spring Anchor Pin Bolt	8-15	6-11

**END PLAY SHIMS (Thickness in Thousandths of an Inch)**

.012	.020	.025	.029	.033	.037	.041
.014	.022	.026	.030	.034	.038	.042
.016	.023	.027	.031	.035	.039	.043
.018	.024	.028	.032	.036	.040	.044

**GEAR RATIOS**

	1st	2nd	3rd	4th	5th	REV
5.0L	3.35	1.93	1.29	1	0.68	3.15
2.3L	3.97	2.34	1.46	1	0.79	3.71

**LUBRICANT**

Type	Capacity	
	Liters	Pints
Dexron II® Series D	2.6	5.6

CC4957-E