



IEEE Standard for Prefixes for Binary Multiples

IEEE Standards Coordinating Committee 14

Sponsored by the
IEEE Standards Coordinating Committee 14 on
Quantities, Units, and Letter Symbols

1541TM

IEEE
3 Park Avenue
New York, NY 10016-5997, USA

18 September 2009

IEEE Std 1541TM-2002

IEEE Standard for Prefixes for Binary Multiples

Sponsor

**Standards Coordinating Committee on
Quantities, Units, and Letter Symbols (SCC14)**

Reaffirmed 27 March 2008

Approved 11 December 2002

IEEE-SA Standards Board

Reaffirmed 13 August 2008

Approved 30 June 2005

American National Standards Association

Abstract: Names and letter symbols for prefixes that denote multiplication of a unit by the binary multiplier 2^{10n} , where $n = 1, 2, 3, 4, 5$, or 6 are defined. Although the prefixes may be used with all units in all fields where multiplication by a binary multiplier is found to be appropriate, their primary use is in the field of information technology.

Keywords: binary, binary multiple, computer, exbi, gibi, kibi, mebi, pebi, prefix, tebi

The Institute of Electrical and Electronics Engineers, Inc.
Three Park Avenue, New York, NY 10016-5997, USA

Copyright © 2009 by the Institute of Electrical and Electronics Engineers, Inc.
All rights reserved. Published 18 September 2009. Printed in the United States of America.

IEEE is a registered trademark in the U.S. Patent & Trademark Office, owned by the Institute of Electrical and Electronics Engineers, Incorporated.

PDF: ISBN 978-0-7381-6106-8 STD95991
Print: ISBN 978-0-7381-6107-5 STDPD95991

No part of this publication may be reproduced in any form, in an electronic retrieval system or otherwise, without the prior written permission of the publisher.

IEEE Standards documents are developed within the IEEE Societies and the Standards Coordinating Committees of the IEEE Standards Association (IEEE-SA) Standards Board. The IEEE develops its standards through a consensus development process, approved by the American National Standards Institute, which brings together volunteers representing varied viewpoints and interests to achieve the final product. Volunteers are not necessarily members of the Institute and serve without compensation. While the IEEE administers the process and establishes rules to promote fairness in the consensus development process, the IEEE does not independently evaluate, test, or verify the accuracy of any of the information or the soundness of any judgments contained in its standards.

Use of an IEEE Standard is wholly voluntary. The IEEE disclaims liability for any personal injury, property or other damage, of any nature whatsoever, whether special, indirect, consequential, or compensatory, directly or indirectly resulting from the publication, use of, or reliance upon this, or any other IEEE Standard document.

The IEEE does not warrant or represent the accuracy or content of the material contained herein, and expressly disclaims any express or implied warranty, including any implied warranty of merchantability or fitness for a specific purpose, or that the use of the material contained herein is free from patent infringement. IEEE Standards documents are supplied “**AS IS.**”

The existence of an IEEE Standard does not imply that there are no other ways to produce, test, measure, purchase, market, or provide other goods and services related to the scope of the IEEE Standard. Furthermore, the viewpoint expressed at the time a standard is approved and issued is subject to change brought about through developments in the state of the art and comments received from users of the standard. Every IEEE Standard is subjected to review at least every five years for revision or reaffirmation, or every ten years for stabilization. When a document is more than five years old and has not been reaffirmed, or more than ten years old and has not been stabilized, it is reasonable to conclude that its contents, although still of some value, do not wholly reflect the present state of the art. Users are cautioned to check to determine that they have the latest edition of any IEEE Standard.

In publishing and making this document available, the IEEE is not suggesting or rendering professional or other services for, or on behalf of, any person or entity. Nor is the IEEE undertaking to perform any duty owed by any other person or entity to another. Any person utilizing this, and any other IEEE Standards document, should rely upon his or her independent judgment in the exercise of reasonable care in any given circumstances or, as appropriate, seek the advice of a competent professional in determining the appropriateness of a given IEEE standard.

Interpretations: Occasionally questions may arise regarding the meaning of portions of standards as they relate to specific applications. When the need for interpretations is brought to the attention of IEEE, the Institute will initiate action to prepare appropriate responses. Since IEEE Standards represent a consensus of concerned interests, it is important to ensure that any interpretation has also received the concurrence of a balance of interests. For this reason, IEEE and the members of its societies and Standards Coordinating Committees are not able to provide an instant response to interpretation requests except in those cases where the matter has previously received formal consideration. A statement, written or oral, that is not processed in accordance with the IEEE-SA Standards Board Operations Manual shall not be considered the official position of IEEE or any of its committees and shall not be considered to be, nor be relied upon as, a formal interpretation of the IEEE. At lectures, symposia, seminars, or educational courses, an individual presenting information on IEEE standards shall make it clear that his or her views should be considered the personal views of that individual rather than the formal position, explanation, or interpretation of the IEEE.

Comments for revision of IEEE Standards are welcome from any interested party, regardless of membership affiliation with IEEE. Suggestions for changes in documents should be in the form of a proposed change of text, together with appropriate supporting comments. Recommendations to change the status of a stabilized standard should include a rationale as to why a revision or withdrawal is required. Comments and recommendations on standards, and requests for interpretations should be addressed to:

Secretary, IEEE-SA Standards Board
445 Hoes Lane
Piscataway, NJ 08854
USA

Authorization to photocopy portions of any individual standard for internal or personal use is granted by The Institute of Electrical and Electronics Engineers, Inc., provided that the appropriate fee is paid to Copyright Clearance Center. To arrange for payment of licensing fee, please contact Copyright Clearance Center, Customer Service, 222 Rosewood Drive, Danvers, MA 01923 USA; +1 978 750 8400. Permission to photocopy portions of any individual standard for educational classroom use can also be obtained through the Copyright Clearance Center.

Introduction

(This introduction is not part of IEEE Std 1541-2002, IEEE Standard for Prefixes for Binary Multiples.)

Modern computers use binary logic for computation and addressing, and binary logic inevitably leads to addresses expressed in binary arithmetic. The size of such an address space is inevitably a power of two. Thus, when computer memories and disks were tiny (in terms of capacity), it became common practice to use “kilo” as a prefix denoting multiplication by 1024 ($= 2^{10}$). In the 1960s and 1970s this created no problem because there is not much difference between 1000 and 1024, and within the community of persons who used computers, everybody understood what was meant. Thus decimal prefixes came to be applied on the grounds that it would have been senseless, in the computer field, to interpret them as anything other than binary multiples, i.e., it would have seemed illogical to size a small memory in multiples of 1000 when the size of the address space was 1024. As the capacity of memories and disks has grown larger, the issue of correspondence with the size of the address space became less important than the issue of total capacity requirements. In addition, the disparity between binary and decimal multiples is larger with the larger prefixes. Data storage specialists now work with terabytes. If one purchases a terabyte of storage, can one store 10^{12} bytes or 2^{40} bytes? The difference is roughly 10%.

Personal computers have become ubiquitous in the twenty-first century, and the use of decimal prefixes where binary multiplication is intended causes real confusion. Most computer users today are not specialists. They know that a kilometer is 1000 meters and, having no familiarity with powers of 2, assume that a kilobyte is 1000 bytes. The result is confusion and occasional misunderstanding. This IEEE standard defines new prefixes for binary multiples and thereby makes precise and unambiguous communication possible. A similar standard, IEC 60027-2 [B1], has already been adopted by the International Electrotechnical Commission.

The working group that prepared this standard had the following membership:

James R. Frysinger, *Chair*

Gordon J. Aubrecht
Bruce B. Barrow
Stanley L. Ehrlich
David Goldman (deceased)

Stan Jakuba
Joseph Langenstein
James W. Moore
John Scott

Ralph M. Showers
Barry N. Taylor
Lorelle M. Young
Allan Zuckerwar

The following members of the balloting committee voted on this standard. Balloters may have voted for approval, disapproval, or abstention.

William W. Aird
O. C. Amrhyn
Gordon J. Aubrecht
Bruce B. Barrow
Norman B. Belecki

Stanley L. Ehrlich
James R. Frysinger
Ronald B. Goldfarb
Dee S. Long
Jack M. Loudon
James McCracken

James W. Moore
Ralph M. Showers
Barry N. Taylor
Theodore Wildi
Lorelle M. Young

When the IEEE-SA Standards Board approved this standard on 11 December 2002, it had the following membership:

James T. Carlo, *Chair*
James H. Gurney, *Vice Chair*
Judith Gorman, *Secretary*

Sid Bennett
H. Stephen Berger
Clyde R. Camp
Richard DeBlasio
Harold E. Epstein
Julian Forster*
Howard M. Frazier

Toshio Fukuda
Arnold M. Greenspan
Raymond Hapeman
Donald M. Heirman
Richard H. Hulett
Lowell G. Johnson
Joseph L. Koepfinger*
Peter H. Lips

Nader Mehravari
Daleep C. Mohla
William J. Moylan
Malcolm V. Thaden
Geoffrey O. Thompson
Howard L. Wolfman
Don Wright

*Member Emeritus

Also included are the following nonvoting IEEE-SA Standards Board liaisons:

Alan Cookson, *NIST Representative*
Satish K. Aggarwal, *NRC Representative*

Noelle D. Humenick
IEEE Standards Project Editor

Contents

1. Overview.....	1
1.1 Scope.....	1
1.2 Purpose.....	1
2. Definitions.....	1
3. Prefixes for binary multiples.....	2
4. Principles of usage	2
4.1 The SI prefixes.....	2
4.2 Application of the prefixes for binary multiples.....	2
Annex A (informative) Bibliography.....	4

IEEE Standard for Prefixes for Binary Multiples

1. Overview

This standard is divided into four clauses. Clause 1 states the scope and purpose of the standard. Clause 2 quotes relevant standard definitions. Clause 3 defines the prefixes for binary multiples. Clause 4 provides principles for the application of these prefixes.

1.1 Scope

This standard defines names and letter symbols for prefixes that denote multiplication of a unit by the binary multiplier 2^{10n} , where $n = 1, 2, 3, 4, 5,$ or 6 . Although the prefixes may be used with all units in all fields where multiplication by a binary multiplier is found to be appropriate, their primary use is in the field of information technology. The prefixes given here have also been adopted by the International Electrotechnical Commission, IEC 60027-2 [B1].¹

1.2 Purpose

In recent years confusion has resulted from the fact that the SI prefixes—kilo, mega, giga, etc.—have been used sometimes with their correct meaning as decimal multipliers and sometimes with a special meaning as binary multipliers. The purpose of this standard is to establish prefixes for binary multiples in order to make precise and unambiguous communication possible, especially within the fields of data processing and information systems.

2. Definitions

For the purposes of this standard, the following terms and definitions, taken from reference IEEE 100 [B2], apply. IEEE 100 should be referenced for terms not defined in this clause.

2.1 byte (B): A group of adjacent binary digits operated on as a unit; usually eight bits.

2.2 octet (o): A byte composed of eight bits.

¹The numbers in brackets correspond to those of the bibliography in Annex A.

3. Prefixes for binary multiples

The prefixes given in Table 1 shall be used to indicate multiplication by 2^{10n} , where $n = 1, 2, 3, 4, 5$, or 6 .

Table 1—Prefixes

Factor	Name	Symbol	Origin	Related SI prefixes		Examples
2^{10}	kibi	Ki	kilobinary: (2^{10})	kilo: (10^3)	k	Kib = 1.024 kb
2^{20}	mebi	Mi	megabinary: $(2^{10})^2$	mega: $(10^3)^2$	M	MiB \approx 1.0486 MB
2^{30}	gibi	Gi	gigabinary: $(2^{10})^3$	giga: $(10^3)^3$	G	Gio \approx 1.0737 Go
2^{40}	tebi	Ti	terabinary: $(2^{10})^4$	tera: $(10^3)^4$	T	Tib \approx 1.0995 Tb
2^{50}	pebi	Pi	petabinary: $(2^{10})^5$	peta: $(10^3)^5$	P	PiB \approx 1.1259 PB
2^{60}	exbi	Ei	exabinary: $(2^{10})^6$	exa: $(10^3)^6$	E	Eio \approx 1.1529 Eo

4. Principles of usage

4.1 The SI prefixes

The SI prefixes shall not be used to denote multiplication by powers of two.

4.2 Application of the prefixes for binary multiples

This standard is prepared with two goals in mind: (1) to preserve the SI prefixes as unambiguous decimal multipliers and (2) to provide alternative prefixes for those cases where binary multipliers are needed. The first goal affects the general public, the wide audience of technical and nontechnical persons who use computers without much concern for their construction or inner working. These persons will normally interpret kilo, mega, etc., in their proper decimal sense. The second goal speaks to specialists—the prefixes for binary multiples make it possible for persons who work in the information sciences to communicate with precision. The following two examples illustrate some of the current confusion.

Example 1: The common 90 mm diskette, as formatted for PC use, is usually advertised as containing 1.44 megabytes.² It is actually formatted for 1440 kibibytes, and the “mega” in this application is neither a proper SI prefix nor a binary prefix. The resulting hybrid “megabyte” is equal to $10^3 \times 2^{10}$ bytes.

Example 2: The following “frequently asked question” appears in an instruction manual widely distributed in 1999:

Q: The formatted capacity of my hard drive seems smaller than what was ordered. Why?

A: Your operating system assumes that 1 MB equals 1 048 576 bytes. Drive manufacturers consider 1 MB as equal to 1 000 000 bytes. Thus, if the drive is advertised as 6.4 gigabytes (6 400 000 000 bytes), the operating system sees it as approximately 6.1 GB $[(6\,400\,000\,000)/(1\,048\,576\,000) = 6.1035\dots]$.

Note that in this example, the PC vendor creates a hybrid “gigabyte” that is equal to $10^3 \times 2^{20}$ bytes.

²The 90 mm diskette has been known by its trade size 3.5 in.

The first example represents more of a curiosity than a real problem, for the difference between the advertised “1.44 MB” and the more accurate 1.47 MB is of little practical importance. The second example, however, calls attention to an area where there has been real misunderstanding between buyers and sellers of hard drives. The difference between a gigabyte and a gibibyte is approximately 7.5%.

Annex A

(informative)

Bibliography

[B1] IEC 60027-2, Letter symbols to be used in electrical technology, Part 2: Telecommunications and electronics, Amendment 2, 1999-01.

[B2] IEEE 100, *The Authoritative Dictionary of IEEE Standards Terms*, Seventh Edition, New York, Institute of Electrical and Electronics Engineers, Inc.³

[B3] IEEE Std 260.1TM-2002, American National Standard Letter Symbols for Units of Measurement (SI Units, Customary Inch-Pound Units, and Certain Other Units).

[B4] IEEE/ASTM SI 10TM-2002, American National Standard for Use of the International System of Units (SI): The Modern Metric System.

³The IEEE standards or products referred to in Annex A are trademarks owned by the Institute of Electrical and Electronics Engineers, Inc.